

The new generation. Stacking Door **SPACELITE® HT 40**

■ Economically priced basic model

For door dimensions up to 5,5 m width by 9,0 m height we offer a cost effective type with basic accessories, which can be extended according to customer's needs and application.

= Flexible modular system

■ Improved thermal insulation

Using the **ISO**-option, we can realize U-values of 1,8 W/m²K for the entire door. This kit contains transparent insertion foils in the fibreglass panels, thermally insulated panel profiles, double sealing to the wall, additional brush sealings inside the guide track and vision panels with filling made of insulation glass.

Hereby the outstanding translucency is hardly affected.

= Significant saving in energy costs

■ Higher opening speed

The **SPRINT**-option with its frequency converter provides a 100% opening speed enhancement.

= More efficient traffic flow and cost savings

■ Updated guide track

Additional positions for sealing profile and brush sealings

= Improved insulation and air tightness

Integrated energy chain

= Maximum reliability even in harsh environment, functional parts are perfectly protected from damages

Mobile fixing brackets

= Perfect for renovations and crowded applications

Guide track heating, easy to retrofit

= Reduced installation costs

Cover sheet easily removable


= Quick and cost effective service



...on top of that the well-known advantages of the Butzbach stacking door system:

■ Translucent fibreglass

= Pleasant working conditions inside the building and reduction of illumination costs



■ Extraordinary opening principle

= Once door is open panels are parked behind the lintel in a space-saving and sheltered manner



■ Low-wear design

No hinges, torsion springs, curly cables or shock absorbers
= Reduces maintenance costs and, at the same time, increases safety for people and material

■ Plenty of sales and service partners abroad

= Service on site is granted